

HS1250 Horizontal Scanner

High Performance Scanning For Any POS Environment

- **For medium-to-high volume grocery, drug, discount and convenience stores, mass merchandisers and home improvement centers**
- **Optimized for horizontal use**

An Exceptional Value

Smart retailers know the true value of a scanner is measured by more than just its price: overall reading performance, cost of ownership, an intelligent design, and quality manufacturing are also important factors in deciding which scanner to purchase.

By any measure, the HS1250 stands out from the crowd as a great value for retailers who demand outstanding performance and reliability at an affordable price.

Small, But Aggressive

The HS1250's aggressive scan pattern and advanced decoding software read all popular bar code symbologies—quickly, accurately and comfortably.

The HS1250 comes standard with UPC/EAN/JAN decoding and advanced Edge™ software for reading torn or disfigured labels. With Edge disabled, the HS1250 reads the UPC family plus one additional industrial code, and reads poorly-printed labels with the help of Adaptive™ software.

At just 7.6" wide by 9.2" inches long, the HS1250 is one of the smallest in-counter scanners you can buy. A generous, forward-leaning scan volume aggressively reads bar codes with minimal orientation of items, providing excellent ergonomics.



And because of its small size, the HS1250 requires minimal checkstand modifications and is compatible with all adaptive shell scales. Plus, every HS1250 includes a flange that enables quick and easy installation into any checkstand—no special brackets are required, which reduces your overall installation costs.

Quality—It's In The Details

When it comes to reliability, the HS1250 goes beyond the competition by including the common sense quality features you expect from PSC.

During manufacturing, every motor is balanced with exacting tolerance to ensure smooth and continuous operation. The scratch-proof inner glass window, volume switch, and external connectors are precision-sealed to protect the scan optics from dust and liquid spills. A Long Life Top (LLT) option keeps the scanner looking like new with stainless steel and a sapphire glass scan window. And for extra durability, the HS1250 is housed in a rugged, cast aluminum enclosure.

Additional Features

- *Peripheral port for undecoded handheld scanner*
- *Programmable sleep mode conserves power and extends scanner life*
- *Effective, easy-to-use diagnostic tools*
- *Low power consumption eliminates need for a fan*
- *Optional EAS antenna for one step scanning and security tag deactivation*

The HS1250: Solid All-Around

Take a closer look at the HS1250—no other horizontal scanner available today features its outstanding combination of high performance, quality design, and easy installation.

PSC[®]

When You Need To Read A Bar Code

HS1250 Horizontal Scanner

SPECIFICATIONS

MECHANICAL

Length	9.2" (23.37 cm)
Width	7.6" (19.30 cm)
Depth	3.45" (8.76 cm)
Weight	5 lbs. (2.3 kg)

OPTICAL

Scan lines	18
Rate	1,350 scans/sec.
Window	20.5 sq. in. (135 sq. cm)
Read height	5" (12.8 cm)

ENVIRONMENTAL

Temperature rating	
• Operating	50° to 104° F (10° to 40° C)
• Storage/transport	-40° to 158° F (-40° to 70° C)
Humidity	
• Operating	5 to 90% NC
• Storage/transport	5 to 95% NC

ELECTRICAL

AC Power requirements	90-265 VAC, 47-63 Hz; 6.4 Watts (nominal), 9.7 Watts (maximum), 4.4 Watts (sleep mode)
-----------------------	---

DECODING CAPABILITY

The HS1250 reads the UPC code family with Edge™ decoding software. When the HS1250 is programmed to read one additional industrial code, Adaptive™ decoding software replaces Edge.

UPC A, E / EAN 8,13 / JAN 8, 13

- with Edge
- Industrial Codes**
- Code 128
 - Code 39
 - ITF (Interleaved 2 of 5)

COMMUNICATIONS

Host	IBM 4682, 4683, 4693; Multidrop (MDL); OCIA; OCIA/IBM dual; OCIA/RS232 dual; RS-232-C; 6-bit; Keyboard Wedge
------	---

Other Peripheral port for undecoded handheld scanner

SAFETY / REGULATORY

Electrical	AS 3260 (Australia); EN60 950 (TUV Europe); Korea Agency; MITI T-Mark (Japan); DEMKO (Denmark); FIMKO (Finland); NEMKO (Norway); SEMKO (Sweden); UL 1950 (USA); cUL C22.2 No. 950-M89 (Canada)
------------	--

Emissions	FCC part 15 subpart j, Class A (USA); AS/NZS 3548 (Australia/New Zealand); VCCI-1 (Japan); VDE Class B, EN 55022-B (Europe)
-----------	---

Laser safety	CDRH Class IIa (USA); IEC 825 Class 1, EN60 825 Class 1 (Europe)
--------------	--

OTHER

EAS compatibility

The optional integrated antenna works with Checkpoint Counterpoint IV, V and subsequent models (available from Checkpoint Systems).

Adaptive scale compatibility

Mettler-Toledo model 8217AS, Avery Berkel model A708 (available from respective manufacturer).



Specifications Subject To Change Without Notice.
For further information, contact your PSC representative.

PSC Worldwide Website: www.pscnet.com

Automation, Self-Checkout and Verification products:

PSC Inc., Corporate Headquarters
675 Basket Road
Webster NY 14580-9787 USA
For Information and Technical Support:
Tel: 1 716 265 1600 or 800 828 6489
Fax: 1 716 265 6400 • E-mail: mktg@pscnet.com



Attended Fixed and Handheld products:

PSC Inc.
959 Terry Street
Eugene OR 97402-9150 USA
For Information:
Tel: 1 541 683 5700 or 800 547 2507
Fax: 1 541 686 1702 • E-mail: mktg@pscnet.com



For Technical Support:
Tel: 1 541 683 5700 or 800 695-8700
Fax: 1 541 984 3092
E-mail: techsupport@pscnet.com

PDT, WMS and Decoder products:

PSC Inc.
1800 Millrace Drive
Eugene OR 97403-1992 USA
For Information:
Tel: 1 541 344 1189 or 800 929 7899
Fax: 1 541 344 1399 • E-mail: info@percon.com

PSC Worldwide Sales and Service locations:

Australia (NSW) Tel: 61 0 2 9878 8999 Fax: 61 0 2 9878 8688	Australia Tel: 61 0 3 9281 3288 Fax: 61 0 3 9243 5519	Belgium Tel: 32 2 414.74.09 Fax: 32 2 410.11.63	Brazil Tel: 55 11 5509-1697 Fax: 55 11 5509-1501	Chile Tel: 562-339-7000 Fax: 562-339-7985	China Tel: 86 10 6857 8699 Fax: 86 10 6857 8699	China (South) Tel: 86 20 8675-99 Fax: 86 20 8675-99	France Tel: 33 01 64 86 71 00 Fax: 33 01 64 46 72 44
Germany Tel: 49 6151 9358-0 Fax: 49 6151 9358 58	Hong Kong Tel: 852-2-584-6210 Fax: 852-2-521-0291	Italy Tel: 39 039 629031 Fax: 39 039 6859496	Japan Tel: 81 0 3 3491-6761 Fax: 81 0 3 3491-6656	Latin America Tel: 1 305 539-0111 Fax: 1 305 539-0206	Singapore Tel: 65-336-8861 Fax: 65-336-6933	Spain Tel: 34 9 1 656 7525 Fax: 34 9 1 656 8485	Sweden Tel: 46 0 40 10 84 90 Fax: 46 0 40 10 84 91
Turkey Tel: 90 212 23691 15 Fax: 90 212 23691 16	United Kingdom Tel: 44 0 1923 809500 Fax: 44 0 1923 809505						

Part No. R45-1610I 0300

PSC and PSC logo are registered trademarks, HS1250 and Edge are trademarks of PSC Inc.
All other brand and product names are trademarks of their respective owners.

Printed in U.S.A.
03/00 - 5K



When You Need To Read A Bar Code